





Series 228

JHK

N

1450rpm

ø 24mm



AR_s228-25_v01

09/10/2024



Series 228

JHK

N

1450rpm

ø 24mm

P	Code	Description		Q	Assembly prescription	Validity	P	Code	Description		Q	Assembly prescription	Validity
1	2289305	Head assembly	Ø 18	1			66	1260430	Ring		1		
2	1381070	Head	nickel plated	1			67	1780690	Plate		1		
3	960870	Plug	1/2" G nickel	1	C=30Nm / Loxeal 55-14		68	1260250	Level gauge		1		
4	180101	O-ring	Ø 17,5x2	1	Lubricate with grease Molykote PG54		69	1140450	O-ring	Ø 20,24x2,62	1	Lubricate with grease Molykote PG54	
5	1981180	Plug	3/8" G nickel	1	C=20Nm / Loxeal 55-14		70	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54	
6	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54		71	2282280	Plug	with magnet	1	C=20Nm	
7	1380690	Plug	1/4" G nickel	2	C=15Nm / Loxeal 55-14		75	2280340	Bearing		1		
8	820510	O-ring	Ø 10,82x1,78	2			76	640030	O-ring	Ø 59,99x2,62	2		
9	4020200	Plug	nickel	6	C=54Nm / Loxeal 55-14		77	1380120	Shim 0.10mm		1		
10	960160	O-ring	Ø 17,86x2,62	6	Lubricate with grease Molykote PG54		77	1380130	Shim 0.19mm		1		
11	1389051	Complete valve		6			77	1380530	Shim 0.25mm		1		
12	880830	O-ring	Ø 15,54x2,62	6	Lubricate with grease Molykote PG54		78	2289020	Cover	complete	1		
20	960110	Ring	support Ø 18	3			79	1941290	Ring		1		
21	2281730	Water seal	Ø 18 PTFE	3			80	1941260	Plate		1		
23	2281750	Piston guide	front Ø 18	3			81	1941270	Level gauge		1		
24	961240	O-ring	Ø 31,47x1,78	3			82	100410	O-ring	Ø 34,6x2,62	1		
25	2281620	Gasket	Ø 18 PTFE	3			84	850370	Screw	TCEI M8x16	4	C=24,5Nm	
27	2281740	Piston guide	rear Ø 18	3			84*	850370	Screw	TCEI M8x16	4	C=24,5Nm	
28	880520	Ring	seal	3			85	2282370	Shaft	4 marked	1		
40	2283610	Pump body		1			86	3200230	Key		1		
41	1383440	Screw	TCEI M8x70	8	C=20Nm		87	1383140	Bearing		1		
42	1381850	Washer		8			89	2340280	Support	open bearing	1		
43	1980740	Plug	3/8" G brass	1	C=20Nm		90	2282261	Ring	seal	1	Assemble with tool [2281010]	
43	880130	Oil plug	with oil dipstick	1			A	2864	Valve kit		1		
44	1980740	Plug	3/8" G brass	1	C=20Nm		B	43402	Piston kit	Ø 18	1		
45	740290	O-ring	Ø 14x1,78	3	Lubricate with grease Molykote PG54		C	43403	Oil seal kit		1		
46	1780510	O-ring	Ø 106x3	1			E	47007	Water seal kit	Ø 18	1		
47	780060	Screw	TCEI M6x25	6	C=10,4Nm		G	1829	Support ring kit	Ø 18	1		
50	1260110	Nut	M8	3	C=12Nm / Loxeal 55-14								
51	1260100	Washer		3									
52	1383230	Piston	Ø 18	3	Lubricate with grease Molykote PG54								
53	480480	O-ring	Ø 4,48x1,78	3									
54	1080550	Ring	anti-extrusion	3									
55	1383350	Plate		3									
56	2282101	Piston	guide	3									
57	1380060	Pin		3									
58	1383020	Connecting-rod	bronze	3									
65	2289021	Cover	complete	1									

Revision: 1

Oil type: SAE 15W40

Validity: < XX/YY = From week/year

Date: 09/10/2024

Oil quantity: 0,515 Kg

C=Tightening torque (Tolerance +0 ÷ -10%)

* = Not present for electric pump

27864 - JHK 13.12 H N