

ST-1200 Low Pressure Cleaning Spray Guns



The choice of perfection

Guns with stepless jet adjustment

Breakproof, shock-proof and robust



ST-1200 low-pressure cleaning guns in four versions

- Inlet: 1/2" F
- Maximum pressure: 24 bar, maximum temperature: 50° C
- Robust rubber coating as protection against heat, cold and shocks
- High-quality workmanship in brass and stainless steel
- Continuously variable jet intensity control using the control lever
- Jet shape adjustment on rear adjustment screw
- With locking clip for continuous use



Rubber protective cover: To protect against impacts and to protect the operator from contact with cold or hot surfaces.

High-quality workmanship: Also available in stainless steel 1.4571 especially for the food industry.



Locking clamp: For continuous operation, to relieve the trigger hand.



Variant with extended insulation at the outlet: Very well thought out for hot water use up to 95°.

With safety guard: protection against unintentional activation of the trigger lever.



functioning of low pressure guns



long casting full jet



conical spray jet



Adjustment: It is not just the trigger that influences the shape of the jet. The jet can also be adjusted using a screw and a coin.

www.rm-suttner.com

ST-1200 Low Pressure Cleaning Spray Guns

Ideal for the agricultural sector or the beverage and food industry

- Wash off coarse dirt in cold or hot water.
- Washing machines, boxes, food containers, etc.
- Locking clamp for continuous flushing.



Suttner low pressure guns

ST-1200 spray guns



Spray gun with adjustable spray angle.
Max. 24 bar / 100 l/min / 50 °C

R+M Nr.	(M)	(C)
201 200 500	brass	1/2" F



Spray gun with adjustable spray angle.
Max. 24 bar / 100 l/min / 50 °C

R+M Nr.	(M)	(C)
500 01	brass/stainless steel	1/2" F



Technical data

Model:	ST-1200
Max. pressure	24 bar
Max. flow	100 l/min
Max. temperature	50° C / 95° C
Material valve housing	brass/stainless steel
Material valve	stainless steel



Spray gun with adjustable spray angle.
Trigger guard. Max. 24 bar / 100 l/min / 95 °C

R+M Nr.	(M)	(C)
201 200 550	brass / stainless steel	1/2" F



Spray gun with adjustable spray angle.
Trigger guard. Max. 24 bar / 100 l/min / 50 °C

R+M Nr.	(M)	(C)
201 200 540	brass/stainless steel	1/2" F