PUReClean365+® Power

high pressure food hoses DN 8





The new high pressure hoses PUReClean365+ Power for hygenic application in the food industry

- PUReClean365+® Food hose according to (EC) 1935/2004, (EC) 10/2011 and (EC) 2023/2006.
- 3-layer plastic hose with a smooth cover
- Premium fabric inlays made of rot-proof synthetic fibre
- Smooth, stain and grease resistant cover
- Excellent ease of use
- Suitable for water and water mixes of usual cleaning detergents
- Particularly pressure-stable and flexible up to a maximum of 200 bar working pressure
- Temperature range: -40 °C +60 °C
- Working pressure: 200 bar
- Fittings stainless steel





Composition: surface made out of thermoplastic elastomer, fabric inlay of synthetic fibre and PES

Technical data **PURe**Clean365+ **Power**

TelkeClean3554 Power DN8 57 EU Nr.10/2011 Sim A WP 200 bar 60°C - 1023 000												
R+M Nr.	DN	P	BP	Roll length	0	Ø	Z	B				
		bar	bar	metres	mm	mm	mm	kg/m				
303 672 00	8	200	> 800	100	7,65	15,3	3,8	0,15				



PUReClean365+® Power

high pressure food hoses DN 8



200 bar >800 bar 15.3 mm 0.15 kg

PUReClean365+® Powe	PUReClean365+® Power per metre						
Female thread DKR 3/8"	Male thread AGR 3/8"	M22 Quick screw couplings	R+M Nr. 303 672 00	DN 8	↔ 100 m	3.8	20
R+M Nr. ↔	R+M Nr.	R+M Nr.					
478 054 610 9 10.0 m	478 044 610 9 10.0 m	478 000 610 9 10.0 m					
478 054 615 9 15.0 m	478 044 615 9 15.0 m	478 000 615 9 15.0 m					
478 054 620 9 20.0 m	478 044 620 9 20.0 m	478 000 620 9 20.0 m					
478 054 625 9 25.0 m	478 044 625 9 25.0 m	478 000 625 9 25.0 m					