

Industrial Water Hose – Highly Flexible Low-Pressure Hose



The choice of perfection



Industrial water hose with exceptional flexibility,
ideal for use in the food industry.

- Very flexible and easy to handle.
- **Hochwertige textile Verstärkung** für hohe **Druckbeständigkeit**.
- **FDA-compliant** synthetic rubber outer cover, **abrasion-, oil-, ozone-, and weather-resistant**.
- DN12: max. **58 bar**
DN19: max. **45 bar**
- Suitable for **animal fats** and **water-based liquids**.
- Temperature range: **-40 °C to +100 °C**.

Perfect for universal applications in food processing, industry, and cleaning systems.

Construction: Inner tube and outer cover made of synthetic rubber. Two layers of high-tensile textile braid.

Smooth Cover: Easy to clean with excellent sliding properties. Highly resistant to abrasion, oil, ozone, and weathering.

Technical Data

| R+M Nr. | DN | ⊙ | | ⌀ | P | | ⤿ | | Ⓢ | ⊠ |
|-------------|----|------|------|------|-----|-----|-----|------|------|-------|
| | | inch | mm | mm | bar | psi | mm | inch | mm | kg/m |
| 305 721 201 | 12 | 1/2" | 12,7 | 19,7 | 58 | 840 | 70 | 2,8 | ~3,5 | ~0,32 |
| 305 723 401 | 19 | 3/4" | 19 | 27 | 45 | 650 | 110 | 4,3 | ~4,0 | ~0,45 |

Symbols DN nominal diameter ⊙ internal diameter ⌀ diameter P pressure ⤿ bending radius Ⓢ weight ⊠ temperature

www.rm-suttner.com