turbodevil

Surface cleaner TD 420 with suction



With suction!

- Cleaning results are visible very quickly and surfaces dry much more quickly
- Extraction behavior like scrubber dryers
- Outdoors for dirty, mossy surfaces, terraces, driveways, etc.
- For interior spaces such as garages, warehouses, industrial and workshop halls and for fire renovation

The turbodevil professional surface cleaner with suction

made

in

GERMANY

SCAN ME

- With suction connection for connection to a vacuum cleaner
- Working width 420 mm
- 2 NPT nozzles 1/4" male are required
- Maximum flow 1,800 l/h •
- Maximum temperature: 90°C •
- Maximum pressure: 350 bar •



For vacuum hose connection sleeves: The connector has an outside diameter of 50 mm and an inside diameter of 45 mm.

Easy-running:							
74 mm swivel							
castors, adjustable.							

High-quality stainless steel design

420 mm large working width: High-quality workmanship made of stainless steel. Suitable for applications up to around 500 operating hours per year.

R+M Nr.	units / pallet	castors ø	working width	inlet	outlet	pressure	temperature	flow	weight
710 100 450	6	4 (74 mm)	420 mm	1/4" M	2 x 1/4" F	max. 350 bar	90 °C	1,800 l/h	13 kg

www.rm-suttner.com

turbodevil

Surface cleaner TD 420 with suction







High-performance swivel joint: For the highest demands with a long service life. Triple ball bearings with extremely high-quality carbide sealing elements.



Easy height adjustment: Guarantees the best possible distance from the ground.



Integrated bracket support: Ensures that the bracket remains in an upright position even during breaks in work and protects attached parts such as the gun and vacuum hose.

Material mix: The use of brushes and rubber lips guarantee clean suction and allow the cleaner to work smoothly. Heat-resistant and protects against splashes and flying particles.



Male thread: For 1/4" connection.



Sophisticated solution: The integrated holding bracket for the vacuum hose ensures easy and safe use without the risk of tripping.

Soft: ergonomic handle.

Holding bracket



We recommend using the gun ST-2605 with our patented

LTF technology.





Low vibration: Balanced rotor arm in robust quality.