



**rotatable inlet:**  
connection suitable for  
right- and left-handed  
users.



ST-2600 **LTF**

We recommend using the  
gun ST-2600 with our  
patented LTF technology.



**suitable wall bracket:**  
R+M Nr. 710 400 156



**clean solution:** the integrated  
screen filter prevents that the  
nozzles get clogged.

## The TurboDevil® surface cleaner with castors for professional use

- high-quality stainless steel design  
with robust ABS cover Ø 520 mm
- easy handling with four castors  
Ø 75 mm
- working width 500 mm
- 2 nozzles 1/4" M BSP are required
- precisely calculated spray angle for  
area-wide cleaning with  
max. 22 l / min at 5 - 90 ° C
- max. temperature: 90 °C
- max. pressure: 250 bar
- weight: 9.0 kg

**new**

**robust  
ABS cover**



**high-quality swivel joint:**  
for professional, industrial use.



**easy handling:** thanks  
to four galvanised swivel  
casters.

**splash protection:** safe  
handling thanks to a  
brush ring. Protects  
against splashes and  
flying stones.

R+M Nr.	units / pallet	working width	inlet	outlet	pressure	flow	temperature	weight
710 520 200	6	500 mm	1/4" F	2 x 1/4" F	max. 250 bar	max. 22 l/min	90 °C	9.0 kg