

# Product Description



PRODUCT NO.: 200078520

## LONGCAST LANCE ST-78 850 MM ST-29



ST-2320 1/2F

With gun ST-2300 1/2" F

Total length: 850 mm

Insulation ST-29 Cool & Compact 330 mm

Nozzle protector without nozzle

Max. 150 bar / 80 l/min. / 100°C

Inlet: 1/2" F

The longcast lance can be connected to a low pressure pump, to a high pressure pump, to the public water system or to the extinguishing water network.

The lance works in the medium pressure range. By means of its very good solidity, good handling and compactness the lance is especially suitable for the intensive use.

The lateral hand grip makes a stepless adjustment of the water jet during the operation possible. A long casting point jet or a progressive, conical spray jet can be set.

In order to realize ideal cleaning results the nozzle size needs to be adapted to the pump performance (pressure and flow rate).

Longcast lance 350 mm with insulation ST-29 Cool & Compact 330 mm, gun ST-2320, grip aside and nozzle protector made out of plastic without nozzle

Inlet: 1/2" F

Outlet: Nozzle protector without nozzle

Total length: 850 mm

Max. 150 bar / 80 l/min. / 100°C

Material: Stainless steel

The longcast lance can be connected to a low pressure pump, to a high pressure pump, to the public water system or to the extinguishing water network.

The lance works in the medium pressure range. By means of its very good solidity, good handling and compactness the lance is especially suitable for the intensive use.

The lateral hand grip makes a stepless adjustment of the water jet during the operation possible. A long casting point jet or a progressive, conical spray jet can be set.

In order to realize ideal cleaning results the nozzle size needs to be adapted to the pump performance (pressure and flow rate)

## Technical data

Color	Black	Flow	80 l/min
Inlet	1/2" F	Manufacturer	Suttner
Material	Stainless steel	Output	Nozzle protector
Pressure	150 bar	Series	ST-78
Temperature	100°C	Type	Standard