

Product Description



PRODUCT NO.: 200160725

EASYWASH365+ FOAM SYSTEM ST-160 KW ST-45




easywash365+ foam set
easywash365+ foam lance standard
Lance with extension ST-9.1 (245 mm)
With injector ST-160 (Coupling ST-45-250 nickel-plated brass, plug ST-45-250 zinc-plated steel and M22 M) with metering valve ST-161
Suction hose 1000 mm and suction filter ST-32
Inlet: 3/8" F swivel
Outlet: Foam head ST-75 (1.9 mm)
Max. 250 bar / 90°C

With LTF technology: LTF - Low Trigger Force 90% reduced holding force and 40% reduced trigger force against usual market guns

The stainless steel injector with high pressure foam lance which is installed via a T-piece between the outlet of the high pressure unit and the original spraying unit is especially designed for the professional cleaning of trucks of shipping or food companies as well as for applications in the industrial foam cleaning.

The connection from injector unit to the high pressure foam lance is realized by an optionally high pressure hose of up to a length of 40 m. The already existing spraying unit is used for cleaning and rinsing works. Enormous savings of both cleaning agent and time can be achieved as the foam lance has cleaning agent immediately available without switching at the unit or change of equipment.

It is possible to simplify the handling of the construction and to boost efficiency at the same time by integrating two hose reels. This set is suitable for all common high pressure cleaning units for up to 310 bar and max. 90°C



Technical data

Nozzle	1,90 mm	Pressure	250 bar
Series	easywash365+®	Temperature	150 °C